

PVC Insulated Wire Lamps

Line No.	Volts	Amps	M.S.C.P	Filament Type	Life Hours
1	1.2	0.300	0.090	C-6	20
2	1.4	0.180	0.080	C-2R	20
3	2.4	0.350	0.600	C-2R	20
4	2.4	0.400	0.800	C-6	6
5	2.5	0.300	0.600	C-2R	15
6	2.5	0.400	0.700	C-2R	30
7	2.7	0.300	0.500	C-2R	20
8	3.0	0.330	1.000	C-2R	20
9	5.0	0.060	0.030	C-2R	100,000
10	5.0	0.060	0.050	C-2R	60,000
11	5.0	0.060	0.150	C-2R	5,000
12	5.0	0.075	0.090	C-2R	25,000
13	5.0	0.115	0.150	C-2R	40,000
14	12.0	0.040	0.150	C-2F	10,000
15	12.0	0.060	0.150	C-2F	16,000
16	14.0	0.040	0.120	C-2F	10,000
17	14.0	0.060	0.200	C-2F	10,000
18	14.0	0.065	0.150	C-2F	16,000
19	14.0	0.070	0.200	C-2F	10,000
20	14.0	0.080	0.300	C-2F	25,000
21	14.0	0.080	0.500	C-2F	1,500
22	14.0	0.100	0.500	C-2F	10,000
23	28.0	0.040	0.300	C-2F	7,000
24	33.0	0.040	0.300	C-2F	10,000
25	48.0	0.025	0.200	CC-2F	5,000
26	60.0	0.020	0.150	CC-2F	5,000